



SIDERMARCA

SIDERMARCA S.R.L.
Via della Libertà, 46
I-31050 Ponzano Veneto (TV)
Tel. +39 0422 96 30 69
Fax +39 0422 96 90 32

P.IVA e C.F. 110238004026/
R.E.A. TV 206888 | Cap. Soc. € 31.200 i.v.
info@sidermarca.com | sidermarca@legalmail.it | www.lucefin.com
Società assoggettata a direzione
e coordinamento da parte di Lucefin S.p.A.



A06 - Customer:	KROKAR D.O.O.	SPODNJI PLAVZ 28	4270 - JESENICE	SLOVENIA
-----------------	----------------------	------------------	-----------------	----------

A02 - Type of inspection document	A03 - Document number	Z02 - Date of issue
Values of the Certificate of Control 3.1 according to EN 10204:2004 Manufacturer	CRT2500017407	28/01/2026

B02 - Grade - B03 - Execution - B01 - Section
S355J2+AR Hot Rolled Round

B02 - Standard of reference (edition in force at the date of the order)	EN 10025-2/04
--	----------------------

B09 - Size [mm]	B03 - Tolerance	B04 - Delivery condition	B05 - Heat treatment
130	EN 10060	+AR	As rolled

A09 - Customer article designation	B08 - Quantity	B10 - Length [mm]
	[kg] 640	6000/6500

B07 - Lot	B07 - Heat	C70 - Stellmaking process	C93 - Reduction ratio of the hot rolled
L25028119	T55852		10,00

A07 - Your Order	A08 - Our Confirmation	A10 - Transport document NR.
9-NAR-26-0076	MRA2601560	MRA2600713 of 28/01/2026

HEAT ANALYSIS											
C71	C72	C73	C74	C75	C76	C77	C78	C79	C80		
C %	Si %	Mn %	P %	S %	Cr %	Mo %	Ni %	Cu %	Al %	CEV%	
0,1800	0,375	1,410	0,0150	0,0260	0,110	0,0070	0,030	0,0300	0,0250	0,44	

Reference mechanical properties of the specimen:
- Heat treatment: +N

Tensile test according to standard EN-ISO 6892

C12 - Rm [MPa]	C11 - Re-Rp 0,2 (*) [MPa]	C13 - A % 5d-L	C14 - Z% L
559,0	391,0	33,00	74,4

* According to the reference standard

Resilienza KV2 -20°C secondo la norma EN-ISO 148 / Impact test KV2 -20°C according to standard EN-ISO 148 / Kerbzähigkeit KV2 -20°C nach Standard EN-ISO 148 / Resilience KV2 -20°C Selon la norme EN-ISO 148

KV2[J]	KV2[J]	KV2[J]
152,0	175,0	149,0

HARDNESS ACCORDING TO STANDARD EN-ISO 6506-1

C30 - HB
C42 - 150

Grain Size ASTM E112	8,00
----------------------	-------------

Z01 - Remarks:

The product supplied complies with the requirements of the order.
This product complies with the Directive 2011/65/EU RoHS II
This product complies with the Regulation (EC) n. 1907/2006 REACH
Material free from radioactive contamination

A05 - Responsible for quality control
Luca Perato